

NEW LONDON AVENUE

STREET INDEX

GENERAL

- I. THIS PLAN IS INTENDED TO PROVIDE GUIDANCE AND INSTRUCTION TO THE OWNER AND CONTRACTOR(S) IN THE PREVENTION OF EROSION AND SEDIMENTATION BOTH ON-SITE AND OFF-SITE. THIS PLAN IS INTENDED TO ALLOW ANY EROSION APPROVALS TO BE MORE SPECIFIC IN ADDRESSING ITEMS OF CONCERN. IF, UPON ISSUANCE OF ANY ORDER, APPROVAL OR PERMIT BY ANY MUNICIPAL, STATE OR FEDERAL ENTITY, ANY ITEMS SPECIFIED HEREIN ARE IN CONFLICT WHICH SUCH ORDERS, SAID ORDERS SHALL SUPERCEDE THE REQUIREMENTS SPECIFIED ON THIS PLAN.
- 2. THIS PLAN IS PART OF A SET OF DOCUMENTS THAT ARE TO BE VIEWED AND REVIEWED IN THEIR ENTIRETY. SUCH DOCUMENTS INCLUDE THE CONSTRUCTION SPECIFICATIONS, CONSTRUCTION PLANS AND ANY PERMITS ISSUED BY THE CITY OF WARWICK OR THE STATE OF RHODE ISLAND, THEIR AGENTS, OR OTHER REGULATORY AGENCIES.

EROSION CONTROL MEASURES

- 1. CONTRACTOR SHALL BE RESPONSIBLE FOR ENSURING THAT EROSION AND SEDIMENTATION ARE CONTROLLED. THIS PLAN SHALL BE ADAPTED TO FIT THE CONTRACTOR'S EQUIPMENT, WEATHER CONDITIONS, AND ANY ORDERS ISSUED BY THE REGULATORY AGENCY HAVING JURISDICTION OVER THIS PROJECT.
- 2. THE MOST IMPORTANT ASPECTS OF CONTROLLING EROSION AND SEDIMENTATION ARE LIMITING THE EXTENT OF DISTURBANCE AND STABILIZING SURFACES AS SOON AS POSSIBLE. OF SECONDARY IMPORTANCE IN EROSION CONTROL IS THE LIMITING OF THE SIZE AND LENGTH OF THE TRIBUTARY DRAINAGE AREA WITHIN THE WORK SITE. THESE FUNDAMENTAL PRINCIPLES SHALL BE THE KEY FACTOR IN THE CONTRACTOR'S CONTROL OF EROSION ON THE SITE.
- 3. ALL DISTURBED SURFACES SHALL BE STABILIZED A MINIMUM OF 7 DAYS AFTER CONSTRUCTION IN ANY PORTION OF THE SITE THAT CONSTRUCTION HAS CEASED OR IS TEMPORARILY HALTED.
- 4. THE CONTRACTOR IS RESPONSIBLE FOR THE MAINTENANCE AND REPAIR OF ALL EROSION CONTROL DEVICES ON SITE. ALL EROSION CONTROL DEVICES SHALL BE REGULARLY INSPECTED. ANY SEDIMENT REMOVED FROM THE CONTROL DEVICES SHALL BE DISPOSED OF OFF-SITE.
- 5. AT NO TIME SHALL SILT-LADEN WATER BE ALLOWED TO ENTER OFF-SITE AREAS OR EXISTING DRAINAGE SYSTEMS. ANY RUNOFF FROM DISTURBED SURFACES SHALL BE DIRECTED THROUGH SETTLING BASINS AND/OR EROSION CONTROL BARRIERS PRIOR TO ENTERING ANY SENSITIVE AREAS.

GENERAL CONSTRUCTION REQUIREMENTS

- I. NO ON-SITE DISPOSAL OF SOLID WASTE, INCLUDING BUILDING MATERIALS, IS ALLOWED. THE BURIAL OF STUMPS, DEMOLITION DEBRIS, CONSTRUCTION DEBRIS OF OTHER MATERIALS SHALL NOT BE ALLOWED ANYWHERE ON-SITE.
- 2. NO MATERIALS SHALL BE DISPOSED OF INTO EXISTING OR PROPOSED SEWER OR DRAINAGE SYSTEMS, EITHER ON-SITE OR OFF-SITE. ALL CONTRACTORS, INCLUDING CONCRETE SUPPLIERS, PAINTERS AND PLASTERERS, SHALL BE INFORMED THAT THE CLEANING OF EQUIPMENT IS PROHIBITED IN AREAS WHERE THE WASH WATER WILL DRAIN DIRECTLY TO OFF-SITE DRAINAGE SYSTEMS.
- 3. THE CONTRACTOR IS RESPONSIBLE FOR DUST CONTROL WHICH SHALL INCLUDE SWEEPING OF ALL PAVED SURFACES THAT ARE IMPACTED BY SITE CONSTRUCTION ON A REGULAR BASIS, AS NEEDED.

PRE-CONSTRUCTION

- I. AN EROSION CONTROL BARRIER SHALL BE INSTALLED AT ANY LOCATION WHERE AREAS TO BE DISTURBED COULD CAUSE EROSION TO OTHER AREAS. THESE BARRIERS SHALL REMAIN IN PLACE UNTIL ALL TRIBUTARY SURFACES HAVE BEEN FULLY STABILIZED.
- THE CONTRACTOR SHALL ESTABLISH A STAGING AREA ON A PORTION OF THE AREA
 TO BE DISTURBED FOR THE OVERNIGHT STORAGE OF EQUIPMENT AND STOCKPILING
 OF MATERIALS.
- 3. IN THE STAGING AREA, THE CONTRACTOR SHALL HAVE A STOCKPILE OF MATERIALS REQUIRED TO CONTROL EROSION ON-SITE, TO BE USED TO SUPPLEMENT OR REPAIR EROSION CONTROL DEVICES. THESE MATERIALS SHALL INCLUDE, BUT ARE NOT LIMITED TO: HAYBALES, SILT FENCE AND CRUSHED STONE
- 4. THE CONTRACTOR IS RESPONSIBLE FOR EROSION CONTROL ON-SITE AND SHALL UTILIZE EROSION CONTROL MEASURES WHERE NEEDED, REGARDLESS OF WHETHER THE MEASURES ARE SPECIFIED HEREIN, ON THE PLAN OR IN ANY ORDERS.

PRELIMINARY SITE WORK

- I. MATERIAL REMOVED SHOULD BE STOCKPILED, SEPARATING THE TOPSOIL FOR FUTURE USE ON THE SITE. EROSION CONTROL SHALL BE UTILIZED ALONG THE DOWNSLOPE SIDE OF THE PILES IF THE PILES ARE TO REMAIN MORE THAN 3 WEEKS.
- 2. STOCKPILES SHALL BE LOCATED WITHIN THE LIMITS OF DISTURBANCE, IN AREAS OF MINIMAL IMPACT. IF A STOCKPILE IS LOCATED ON A SLOPE, THE RUNOFF SHALL BE DIRECTED AWAY FROM THE PILE
- 3. IF INTENSE RAINFALL IS ANTICIPATED, THE INSTALLATION OF SUPPLEMENTAL HAYBALE DIKES, SILT FENCES, OR ARMORED DIKES SHALL BE UTILIZED.


RAIN GARDEN CALCULATIONS:

ROOF IMPERMEABLE TRIBUTARY AREA = 1,500 S.F.
TRIB. AREA TO GARDEN SQUARE FOOTAGE CONVERSION = 0.16

*FROM RI SMG TABLE 10 1,500 S.F. * 0.16 = 240 S.F. RAIN GARDEN REQUIRED

22 FT. * 11 FT. = 242 S.F. RAIN GARDEN PROPOSED

2:1 LENGTH TO WIDTH RATIO RECOMMENDED PER RI SMG LENGTH=22 FT., WIDTH=11 FT.



VEGETATED SWALE DETAIL

Dissans

ATTER

Closeins

RAIN GARDEN LOW SLOPE CONSTRUCTION

VEGETATED SWALE CALCULATIONS:

*FROM RI SMG TABLE 5.

LENGTH = 15 FT, WIDTH = 8 FT.

DRIVEWAY IMPERMEABLE TRIBUTARY AREA = 635 S.F. ~ 700 S.F.

TRIB. AREA TO GARDEN SQUARE FOOTAGE CONVERSION = 0.16*

700 S.F. * 0.16 = 112 S.F. VEGETATED SWALE REQUIRED.

15 FT. * 8 FT. = 120 S.F. VEGETATED SWALE PROPOSED.

ZONING DISTRICT A-7 MINIMUM LOTAREA: 7,000 S.F.

MINIMUM LOT FRONTAGE: 70 FT.
MINIMUM SETBACKS: FRONT: 25 FT.
SIDE: 8 FT.
REAR: 20 FT.

LOCUS MAP

NOT TO SCALE

MAXIMUM STRUCTURE HEIGHT: 35 FT. MINIMUM LANDSCAPE: 10%

SEWER MANHOLE B.M. = 99.93RAIN GARDEN TO BE ASSUMED DATUM PLANTED IN ACCORDANCE WITH THE RHODE ISLAND COASTAL PLANT GUIDE RAIN GARDEN EXAMPLE PLANTING CONSTRUCTION \ **ENTRANCE** SEE RI 9.9. FLOW -15.0' PARCEL 2 30.5 /PROPOSED A.P. 251 / LOT 54 SINGLE 14,000 S.F. **VEGETATED FAMILY SWALE DWELLING** (15' x 8') 100.00 200.00 100.00'

SURVEY CLASSIFICATION:

THIS SURVEY HAS BEEN CONDUCTED AND THE PLAN HAS BEEN PREPARED PURSUANT TO SECTION 9 OF THE RULES AND REGULATIONS ADOPTED BY THE RHODE ISLAND STATE BOARD OF REGISTRATION FOR PROFESSIONAL LAND SURVEYORS ON NOVEMBER 25, 2015, AS FOLLOWS:

TYPE OF BOUNDARY SURVEY:
LIMITED CONTENT BOUNDARY SURVEY

SUBDIVISION TO THE EXISTING PARCELS.

MEASUREMENT SPECIFICATION:


THE PURPOSE FOR THE CONDUCT OF THE SURVEY AND FOR THE PREPARATION OF THE PLAN IS AS FOLLOWS:


TO ESTABLISH AND STAKE RECORD, BOUNDARY LINES, AS TO PROPOSE A

RICHARD T. BZDYRA, PLS; LICENSE #1786; COA # LS-A60

BY: DATE: 9/21/21

I HEREBY CERTIFY THAT HIS SURVEY WAS ACTUALLY MADE ON THE GROUND AS PER RECORD DESCRIPTION AND IS CORRECT. THERE ARE NO ENCROACHMENTS EITHER WAY ACROSS PROPERTY LINES EXCEPT AS SHOWN. LOTS DEPICTED ON THIS PLAT SHALL NOT BE ALTERED DIMENSIONALLY OR IN FORM, INCLUDING THE ENLARGEMENT OF LOTS OR MOVING OF ANY LOT LINE FOR ANY PURPOSE WHATSOEVER, WITHOUT FIRST FILING A NEW SUBDIVISION APPLICATION IN ACCORDANCE WITH THE CITY OF WARWICK DEVELOPMENT REVIEW REGULATIONS OF DECEMBER 31, 1995.





REPLAT OF "WOODLAWN PLAT" MINOR SUBDIVISION PRELIMINARY PLAN

SOIL EROSION & SEDIMENTATION CONTROL PLAN

A.P. 251 / LOTS 54, 55, 60, 61 & 62 131 NEW LONDON AVENUE WARWICK, R.I. 02886

SCALE: 1" = 20' DATE: SEPTEMBER 20, 2021

PREPARED FOR:

PANCAROWICZ FAMILY TRUST

37 SANDY BOTTOM ROAD, COVENTRY, R.I. 02816 PHONE: (401) 465-0263

PREPARED BY:

OCEAN STATE PLANNERS, INC.

1255 OAKLAWN AVENUE, CRANSTON, RI 02920 PHONE: (401) 463-9696 info@osplanners.com

JOB NO. 9559 / DWG. NO. 9559 - PP - (AJB/CJB) SHEET: 3 OF 4

GRAPHIC SCALE / 1" = 20'

0 20 40 6

